## Hybrid RBF training algorithm based on artificial immunology

CONG Xin-bao, ZANG Xiao-gang, ZHOU\_Xi-lang

(Department of Electronic Engineering, Shanghai Jiaotong University, Shanghai 200030, China)

Abstract : Based on artificial immune clustering and Immune Evolutionary Aigorithm (IEA), a novel hybrid RBF design method is proposed. The artificial immune clustering is used to adaptively specify the amount and initial position of centers of basis functions in RBF network according to input data set. Then immune evolutionary algorithm is used to train the RBF network, which reduces the searching space of canonical evolutionr ary algorithm and improves the convergence speed. Computer simulations demonstrate that the RBF network designed in this method has a concise structure with good generalization ability.

Key words : Artificial immune clustering ;Immune evolutionary algorithm ;RBF networkCLC number : TP183Document code : AArticle ID :1007-2276 (2004) 03-0311-05

## 基于人工免疫机制的 RBF 网络混合训练算法

宫新保, 臧小刚, 周希朗 (上海交通大学 电子工程系,上海 200030)

摘要:基于人工免疫聚类机制和免疫进化算法,提出了一种新型的设计 RBF 网络的混合算法。 该方法利用人工免疫聚类机制,根据输入数据集合自适应地确定 RBF 网络核函数的数量及其中心 的初始位置。采用免疫进化算法训练 RBF 网络,进一步缩小了标准进化算法搜索空间的范围,提 高了算法的收敛速度。计算机仿真表明,这种 RBF 网络结构精简并具有较强的泛化能力。

关键词:人工免疫聚类; 免疫进化算法; 径向基函数网络

### 0 Introduction

Radial Basis Function (RBF) network<sup>[1]</sup> has been widely used in pattern recognition, function regression, signal processing and system control, etc. In RBF network

the centers and width of the basis functions in the hidden layer have great influence on the performance of the network, but common RBF training algorithms cannot find the global optima of the network, and will often have too many hidden units to reach certain approximate ability, which

收稿日期:2003-10-15; 修订日期:2003-12-06

作者简介:宫新保(1967-),男,讲师,山西大同人,主要研究方向为进化计算及无线通信。

will lead to too large scale for the network and the decline of generalization ability.

In order to solve the problem, a hybrid method combined with artificial immune clustering<sup>[2]</sup> and Immune Evolutionary Algorithm (IEA)<sup>[3]</sup> is used to design the RBF network. Combining fuzzy C-means clustering method with immune algorithm, the immune clustering method can adaptively specify the amount and initial positions of the RBF centers according to input data set. IEA is then used to train the RBF network. The algorithm extracts the preliminary knowledge about the width of the basis function as the vaccine to form the immune operator, which reduces the searching space of canonical evolution algorithm. The applications of the RBF network designed with the hybrid method in the radar-scanning style recognition problem demonstrate the good performance of the network.

#### 1 **RBF** net work

RBF network is a three-layer feedforward neural network including a single hidden layer. For a p-dimensional input vector  $\mathbf{x}_i = (x_1, x_2, ..., x_p)$ , where  $\mathbf{x}_i \quad \mathbf{X} \subset \mathbf{R}^p$ , the output of the RBF network can be computed as follows

$$y_{i} = \mathbf{w}_{i}^{\mathsf{T}} \mathbf{g} = \int_{j=1}^{m} w_{ij} \exp\left[-\frac{\mathbf{x} - \mathbf{z}_{j}}{2}\right]$$
$$i = 1, ..., o, j = 1, ..., m$$
(1)

where  $w_i = [w_{i1}, \dots, w_{im}]^T$  is the *i*th weight vector from hidden layer to the output layer,  $g = [g_1, g_2, \dots, g_m]^T$  is the vector of Gaussian basis functions, with centers  $z_j$  $\mathbf{R}^p$  and width *i*, *o* is the number of network output units.

The positions of center  $z_j$  and width  $_j$  have great impact on the performance of RBF network. But common RBF training algorithms have the possibility of only reaching the poor local minimum of the network, which will degrade the performance of the system. Therefore, a hybrid method is proposed in the paper to design the RBF network.

## 2 Description of the hybrid algorithm

The major steps of the hybrid algorithm can be described as the following

(1) Generate an initial population  $A_1$  using real number encoding, where each individual in  $A_1$  is corresponding to a certain network structure. The amount and initial positions of center  $z_j$ , j = 1, ..., m in RBF network are determined by artificial immune clustering, while the width j, j = 1, ..., m and weight vector  $w_i$ , i = 1, ..., o are initialized randomly.

(2) Extract vaccine according to preliminary knowledge.

(3) Compute the fitness function of each individual. If the current individual is acceptable or the maximum number of generations has been reached, stop the evolutionary process, otherwise continue.

(4) Perform mutation on the current population  $A_k$ and obtain the results  $B_k$ .

(5) Perform vaccination on  $B_k$  and obtain  $C_k$ . "Vaccination" is to select certain individuals from the current population according to certain percentage and change certain gene bits of the selected individuals according to the vaccine extracted in step (2), so as to improve their fitness.

(6) Perform immune selection on  $C_k$  and obtain the next population  $A_{k+1}$ , then go to step (3). Immune selection is to perform the fitness test on the individuals after vaccination, and select best individuals into the next population.

The fitness of each individual is determined by f = 1/E, where *E* is the error function of the network

$$E = \sum_{t=1}^{N-o} (Y_i(t) - \overline{Y}_i(t))^2$$
(2)

where  $Y_i(t)$  and  $\overline{Y}_i(t)$  are the actual and desired outputs

of node *i* for input pattern t, o and N are the number of output nodes and input patterns, respectively. Artificial immune clustering in step (1) and vaccine extraction in step (2) are introduced in section 3 and section 4, respectively.

## 3 Specify RBF centers with artificial immune clustering

Artificial Immune Clustering(AIC) is used in the paper to specify RBF centers<sup>[2]</sup>. Assume that the training data set has *N* input vectors,  $X = \{x_1, x_2, ..., x_N\}$ ,  $x_i \mathbb{R}^p$ . The problem is to find a new set  $Z = \{z_1, z_2, ..., z_m\}$  composed of *m* patterns to form the centers of RBF network. It is hoped that the elements in Z can cover all the input vectors in space  $\mathbb{R}^p$ , while the distances among the elements in Z is as far as possible. In the algorithm, each input vector  $x_i$ , i = 1, ..., N in X corresponds to an antigen (Ag), while each candidate center  $z_j$ , j = 1, ..., m in Z corresponds to an antibody (Ab). Matching degree (affinity) among the vectors is measured by their Euclidean distance in space  $\mathbb{R}^p$ ; the smaller the distance, the greater the affinity is among the vectors.

Immune algorithm<sup>[2]</sup> is an improved evolutionary algorithm based on immunity. Inspired by somatic theory and immune network theory, immune algorithm realizes the self-control mechanism and diversity similar to natural immune system. Compared to other heuristic optimization algorithms, immune algorithm improves the searching ability through immune memory mechanism and combats the immature convergence through affinity calculation. In immune clustering algorithm, the antigen and the antibody correspond to the objective and the feasible solution, respectively.

The objective function of fuzzy C-means (FCM) is

$$I(\mathbf{X};\mathbf{U},\mathbf{Z}) = \sum_{k=1}^{N} u_{ik}^{F} D_{ik}^{2}$$
(3)

$$D_{ik}^{2} = (x_{k} - z_{i})^{T}(x_{k} - z_{i})$$
(4)

where  $D_{ik}$  is the distance of *k*th input data to *i*th RBF center.  $Z = \{ z_1, z_2, ..., z_m \}$  denotes the centers of RBF network. *F* is fuzzy exponent.  $X = \{ x_1, x_2, ..., x_N \} \subset \mathbf{R}^p$  denotes the input pattern. U is defined as

$$U = \{ U \quad \mathbf{R}^{M \times N} / u_{ik} \quad [0,1], \forall i, k; \\ 0 < \sum_{k=1}^{N} u_{ik} < N, \forall i \}$$

In the immune clustering algorithm, clustering centers Z is encoded. Fitness function is constructed as

$$f_c = \frac{1}{J(X; U, Z) + 1}$$
 (5)

The fuzzy C-means clustering based on immune algorithm (IFCM) can be described as

(1) Specify number of RBF initial centers Z and fuzzy exponent *F*, where 1 *m N* - 1 and *F* (1, + ). Set stop criterion  $S_c$ , crossover probability  $P_c$  and mutation probability  $P_m$ . Produce initial antibody population P(k), k = 0.

(2) Calculate affinities : calculate the affinity  $ax_v$  between antigen and antibody v, the affinity  $ax_{v,w}$  between antibody v and w.

1) Decode each individual and compute prototype parameter  $\{z_i, 1 \ i \ m\}$ .

2) Compute  $D_{ik}^2$  according to equation (4)

3) U =  $[u_{ik}]_m \times N$  can be computed as

$$I_{k} = \phi \Rightarrow u_{ik} = 1 / \int_{j=1}^{m} \left[ \frac{d_{ik}^{2}}{d_{jk}^{2}} \right]^{\frac{1}{F-1}}$$
$$I_{k} \qquad \phi \Rightarrow u_{ik} = 0, \forall i \qquad \overline{I}_{k}, \quad u_{ik} = 1$$

where  $I_k = \{ i | 1 \ i \ m, d_{ik} = 0 \}$ ,  $\overline{I}_k = \{ 1, 2, ..., m \} - I_k$ .

4) Calculate J(X; U, Z) and  $f_c$ .

(3) Update memory repertoire: the antibodies that show high affinity with the antigen are added in the memory repertoire.

(4) Promotion and suppression of antibody-production : the expectation value  $e_i$  of antibody *i* is calculated, and the antibodies that have low expectation values are extinguished.

$$e_i = \frac{ax_i}{c_i}$$

where  $c_i$  is the density of antibody *i*.

(5) Update antibodies: according to the expectation value, new generation of antibodies P(k + 1) are produced through mutation and crossover on P(k).

(6) Termination criterion: if the termination criterion  $S_c$  is satisfied, the clustering procedures end.

# 4 Immune evolutionary algorithm and vaccine extraction

The evolutionary algorithm is a kind of generationand-test algorithm. On condition of preserving the advantages of evolutionary algorithm, the immune evolutionary algorithm utilizes some characteristics and knowledge in the pending problems for restraining the degenerative phenomena during evolution, so as to improve the algorithmic efficiency. The core of the immune algorithm is the construction of the immune operator, which is realized through two steps, i.e., vaccination and immune selection.

The width has great impact on the RBF network performance. In the algorithm, the approximate range of is used as the vaccine to reduce the searching space and improve the fitness of population. The vaccine is extracted as follows

(1) Use artificial immune clustering described in sec-

tion 3 to specify the positions and amount of RBF Centers. Assuming all the basis functions have the same , let have different values in the possible range according to the same length. For instance, let start from 0.1, and length is 1, and equal to 0.1, 1.1, 1.2...,respectively.

(2) Compute different interpolation matrix G corresponding to the training data sets for different . Using regression procedure to compute linear output weight matrix w according to the equation

$$Gw = d$$
 (6)

Where d is the desired outputs of the training data.

(3) Compute the fitness of the RBF networks usingdifferent . In a certain range centered on the best , repeat step (1) and (2).

Generally speaking, iteration of two times for the above algorithm is enough. This is because we can only estimate the possible range of . If the range is too small, we can possibly get the wrong vaccine.

### 5 Simulations

The RBF network designed with the hybrid method suggested in the paper is applied in the radar-scanning style recognition problem. Fast recognition of scanning style of radar antennas is very important in modern electronic warfare. In essence, the recognition of scanning style is based on the character parameters of radar signals after pre-processing. Typical signal parameters influenced by scanning styles include<sup>[4]</sup>: zenith of radar impulses  $P_{\text{max}}$ , scanning period of radar antennas T, time intervals between the zenith of different impulses T and the width of radar impulses  $T_s$ .

In simulation the RBF networks have 4 input nodes, corresponding to 4 input signal parameters. The network is trained with 80 samples and then tested with 500 sam-

ples. The Wrong Recognition Rate/*SNR* curves of radar scanning style recognition by RBF networks trained with the hybrid algorithm, Evolutionary Programming  $(EP)^{[5]}$ , *k*-means<sup>[6]</sup> and OLS<sup>[7]</sup> algorithms are shown in Fig. 1. It can be seen that the RBF network trained with hybrid algorithm has the best recognition rate , demonstrating the strong gerr eralization ability of the network.



Fig. 1 Wrong Recognition Rate/ SNR of radar scanning style recognition

#### 6 Conclusion

A hybrid evolutionary RBF network based on artificial immune clustering and IEA is proposed in the paper. The artificial immune clustering is used to adaptively specify the amount and initial centers of basis functions in RBF network. Then immune evolutionary algorithm is used to train the RBF network. The applications of the RBF network in radar-scanning style recognition problem demonstrate the efficiency of the algorithm.



- Bernard Mulgrew. Applying radial basis functions[J]. IEEE Signal Processing Magazine, 1996, 13(2): 50-65.
- [2] Jang Sung Chun, Min Kyu Kim, Hyun Kyo Jung. Shape optimization of electromagnetic device using immune algorithm[J]. IEEE Transaction on Magnetics, 1997, 33(2):1876-1879.
- [3] Jiao Licheng, Wang Lei. A novel genetic algorithm based on immunity
  [J]. IEEE Trans on Systems, Man and Cybernetics, 2000, 30(5): 552-561.
- [4] D Curtis Schleher. Electronic warfare in the information age[M]. USA: Artech House, 1999.
- [5] Angeline P J , Saunders G M, Pollack J B. An evolutionary algorithm that constructs recurrent neural networks[J]. IEEE Trans on Neural Networks, 1994, 5(1): 54-64.
- [6] Moody J , Darken C. Fast learning in networks of locally-tuned processing units[J]. Neural Computation, 1989,1(2): 281-294.
- [7] Chen S, Cowan C F N, Grant P M. Orthogonal least squares learning algorithms for radial basis function networks [J]. IEEE Trans on Neural Networks, 1991, 2(2): 302-309.

## 《红外与激光工程》中文文摘编写要求

本刊中文文摘按 GB6447-86《文摘编写规则》编写,编写文摘应注意:

1. 文摘应包含目的、方法、结果和结论四要素。目的是指主题范围;方法是指所用的原理、工艺、材料、手段、装备等;结果是指实验研究的分析、评价、建议等。篇幅为 200~300 字。

- 2. 结构严谨,表达简明,语义确切。一般不分段落。
- 3. 文摘一律用第三人称,应采用"介绍了…","对…进行了研究",不必使用"本文\*\*作者"等作为主语。
- 4. 文摘应具有独立性、自含性,不标注图、表、公式和参考文献的序号。
- 5. 要采用规范化的名词术语,第一次出现非公知的术语时应标注说明。
- 6. 缩略语、略称、代号除读者能清楚的以外,首次出现时必须加以说明。
- 7. 应采用国家颁布的法定计量单位。
- 8. 要注意正确使用简化字和标点符号。
- 9. 中文摘要前加"摘要"作为标识。